

# SSG3000X Pulse Modulation Spec Clarification

July 20, 2022

The Pulse Modulation states:

Modulation frequency response	10 Hz~100 kHz	<3 dB (nom.)
<b>Pulse modulation</b>		
Modulation source	internal, external	
On/off ration	1 MHz <f<3.2 GHz	>70 dBc
Raise/fall time (10% / 90%)	10% to 90% of RF amplitude	<50 ns
Pulse repetition time	setting range	40 ns~300 s
<b>Pulse generator</b>		

The SSG3000X Pulse Modulation is functional from 9 kHz to 2.1/3.2 GHz. The specification of 1 MHz- 3.2 GHz is guaranteed (as shown). Operation from 9 kHz-1 MHz is not guaranteed.



### **North American Headquarters**

SIGLENT Technologies America, Inc  
6557 Cochran Rd Solon, Ohio 44139  
Tel: 440-398-5800  
Toll Free:877-515-5551  
Fax: 440-399-1211  
[info@siglent.com](mailto:info@siglent.com)  
[www.siglentamerica.com/](http://www.siglentamerica.com/)

### **European Sales Offices**

SIGLENT TECHNOLOGIES EUROPE GmbH  
Staetzlinger Str. 70  
86165 Augsburg, Germany  
Tel: +49(0)-821-666 0 111 0  
Fax: +49(0)-821-666 0 111 22  
[info-eu@siglent.com](mailto:info-eu@siglent.com)  
[www.siglenteu.com](http://www.siglenteu.com)

### **Asian Headquarters**

SIGLENT TECHNOLOGIES CO., LTD.  
Blog No.4 & No.5, Antongda Industrial Zone,  
3rd Liuxian Road, Bao'an District,  
Shenzhen, 518101, China.  
Tel:+ 86 755 3661 5186  
Fax:+ 86 755 3359 1582  
[sales@siglent.com](mailto:sales@siglent.com)  
[www.siglent.com/ens](http://www.siglent.com/ens)